


Specifications

MODELS	DPL™-25S		DPL™-30S		DPL™-35S	
MEASUREMENTS	Metric	US	Metric	US	Metric	US
Working height*	9.70 m	31 ft 4 in	11.14 m	36 ft	12.06 m	40 ft 9 in
Platform height	7.70 m	25 ft 4 in	9.14 m	30 ft	10.06 m	34 ft 9 in
Height - stowed	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
Length - stowed	2.08 m	6 ft 9.75 in	2.08 m	6 ft 9.75 in	2.08 m	6 ft 9.75 in
Width	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in
PRODUCTIVITY						
Lift capacity: CE (European)	340 kg	750 lbs	340 kg	750 lbs	272 kg	600 lbs
Outrigger footprint:						
A length	2.08 m	6 ft 10 in	2.19 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in
B width	1.44 m	4 ft 8.5 in	1.75 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in
C corner access	43 cm	1 ft 5 in	61 cm	2 ft	61 cm	2 ft
D wall access front	18 cm	7 in	23 cm	9 in	23 cm	9 in
E wall access side	41 cm	1 ft 4 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in
Platform length	1.83 m	6 ft	1.83 m	6 ft	1.83 m	6 ft
Platform width	70 cm	2 ft 3.5 in	70 cm	2 ft 3.5 in	70 cm	2 ft 3.5 in
POWER						
Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz					
DC models	12 V					
WEIGHT**						
AC	1,375 lbs	624 kg	1,475 lbs	669 kg	1,575 lbs	714 kg
DC	1,450 lbs	658 kg	1,550 lbs	703 kg	1,650 lbs	748 kg
STANDARDS COMPLIANCE						
	CE EN280					



* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Weight will vary depending on options and/or country standards

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- 1.83 m x 70 cm (6 ft x 2 ft 3.5 in) platform

POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 amp battery

STANDARD FEATURES

MEASUREMENTS

DPL™-25S

- 9.70 m (31 ft 4 in) working height
- 7.70 m (25 ft 4 in) platform height
- 80 cm (2 ft 7.5 in) base width
- 272-340 kg (600-750 lb) lift capacity

DPL™-30S

- 11.14 m (36 ft) working height
- 9.14 m (30 ft) platform height
- 80 cm in (2 ft 7.5 in) base width
- 272-340 kg (600-750 lb) lift capacity

DPL™-35S

- 12.06 m (40 ft 9 in) working height
- 10.06 m (34 ft 9 in) platform height
- 80 cm (2 ft 7.5 in) base width
- 227-272 kg (500-600 lb) lift capacity

PRODUCTIVITY

- Large platform
- AC power to platform
- Auxiliary platform lowering
- Dual activated up/down switch
- Ground fault interrupt power receptacle
- Most rigid mast in the industry
- Durable base system
- Angled entry ladder
- LED lights confirm proper setup of outriggers
- Patented outrigger interlock system
- Swivel-lock casters
- Easily rolls through standard doorways
- Outrigger storage pockets
- Multi-direction forklift pocket access
- Winch attachment points
- Tie down attachment points
- Locking key switch
- Fully certified load sensor

POWER

- DC models include a 15 amp charging system with 110 V / 50-60 Hz or 220 V / 50-60 Hz input voltages



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Platform locating laser light
- Tool tray
- Fluorescent tube caddy
- Operational warning light and descent alarm package

POWER

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 Amp battery

Distributed By:

European Offices

UK

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-20

Spain

Gaià 31, Pol. Ind. Plà d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Tagenevägen 72
425 37 Hisings Kärra
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 90 20

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
USA
Tel: +1 425 881-1800
Fax: +1 425 883-3475

WEB: www.genieindustries.com
Email: infoeurope@genieind.com